WH30006000-100W (3000~6000MHz, 100W)

The WH30006000-100W is covered wide band frequency 3,000 to 6,000MHz with minimum Psat 100W across the specified Temperature range and environmental condition. This is suitable for testing in Laboratory as Drive HPA and jamming in S, C frequency band. This compact module utilizes high power advanced Wavice RF GaN devices that guaranteed excellent power density and low distortions. Outstanding performance and long-term reliability are applied by employing advanced broadband RF matching networks and combining techniques. This compact module utilizes the latest high power Wavice RF GaN transistors and also features built-in control and monitoring, with protection functions to ensure high availability.

▶ Features

- Saturated power 100W Typ.
- Wide bandwidth, 3000 to 6000 MHz
- High gain, 55 dB typ.

ELECTRICAL SPECIFICATIONS @ +50 VDC, 25°C, 50 Ω System

Parameter	Symbol	Min	Typ	Max	Unit
Operating Frequency	BW	3000		6000	MHz
Output Power @CW	P_{SAT}	80	100		W
Small Signal Gain	G_{ss}		55		dB
Power Gain Flatness	ΔG		±3.0		dB
Input return loss	S_{11}			-10	dB
Operating Voltage	V_{DC}	48	50	52	V
Current Consumption @Pout = 100W	I_{DD}		15	20	A
Quiescent Current	I_{DQ}		3.0		A

ENVIRONMENTAL CHARACTERISTICS (Design to meet)

Parameter	Symbol	Min	Typ	Max	Unit
Operating Case Temperature	T_c	-20		+50	°C

MECHANICAL SPECIFICATIONS

Parameter	Value	Units	Limits
Dimension (W x L x H)	200 x 150 x 25	mm	
RF Connectors In/Out	Input : SMA(Female), Output : N(Female)	-	
Interface Connector	D-Sub 7W2(Male)	-	
Cooling	External Heatsink	-	

INTERFACE CONNECTOR – D-Sub 7W2, Male

Pin #	Description	Specifications
1	NC	NC
2	Current Monitor	Outputs analog voltage related to main current @10mV / 100mA
3	Temp Monitor	Outputs analog voltage related to temperature @10mV/˚C + 500mV
4	NC	NC
5	Shutdown	Low enable, High Disable (3.3V), Internally pull down
A1	VDD	+50VDC
A2	GND	GND

Copyright © 2017 Wavice Inc. All rights reserved. The information in this document is subject to change without notice.

46, Samsung 1-ro 5-gil, Hwaseong-si, Gyeonggi-do, Korea(18449)
Tel : +82-31-260-8600, Fax : +82-31-260-8699, E-mail : sales@wavice.com

OUTLINE DRAWING



[Unit : mm]

Disclaimer

Specifications are subject to change without notice. Wavice Inc. believes the information contained within this data sheet to be accurate and reliable. However, no responsibility is assumed by Wavice for any infringement of patents or other rights of third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of Wavice. Wavice makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose. “Typical” parameters are the average values expected by Wavice in large quantities and are provided for information purposes only. These values can and do vary in different applications and actual performance can vary over time. Customers should obtain and verify the latest relevant information before placing orders for Wavice products. All operating parameters should be validated by customer’s technical experts for each application.

Wavice products are not designed, intended or authorized for use as critical components in life-saving, or life-sustaining applications or other applications in which the failure of Wavice product could result in severe personal injury or death or in applications for planning, construction, maintenance or direct operation of a nuclear facility.

Copyright © 2017 Wavice Inc. All rights reserved. The information in this document is subject to change without notice.